

Our Third-Generation Thin Clients Pack Big Features in a Small Footprint



The new YES_{tation} Mini family of thin clients just raised the bar for performance, while lowering the desktop space requirement. Built around an Intel®-compatible SIS 550 processor that can run either Windows® CE.NET or Linux operating systems, the new hardware platform is 35% smaller, 20% faster, uses 30% less power and is 29% less expensive than other thin clients.

YES_{tation} Mini has a very small footprint – only 7.75" by 6" by 1.5" – and can be mounted vertically on a wall or attached to a monitor. The unit weighs only 1.5 pounds allowing for optimal mounting options, and low shipping costs.

The YES_{tation} Mini model 2205 provides ICA and RDP clients for connections to Windows Terminal Services and Citrix servers as well as an embedded Internet Explorer 5.5 browser (previously an extra cost option) for access to Web-enabled applications, including email. Priced at \$395, it is the lowest-priced Internet Terminal for IBM iSeries and OS/400 users running Client Access, Rumba or other server based emulators. Terminal style 122-key, 5250/PC keyboards are supported by installing Affirmative's keyboard drivers and map files.



Mounting options include vertical or horizontal orientations and monitor integration.

All YES_{tation} Windows Based Terminals (WBT) include CE.NET, which has several new features not available with CE 3.0, including a secure VPN client and support for USB disk drives. Other free features include Acrobat Reader and Microsoft® Office Viewer clients for display and print of PDF, Word, Excel, Access and Powerpoint files received as email attachments or from Internet/Intranet sessions.

The YES_{tation} Mini is 35% smaller than competitive Thin Clients. ▼



The YES_{tation} Mini's advanced technology provides the best price/performance in the industry.

Backed by Affirmative's superior technical support and six years of thin client experience with AS/400 and iSeries users, the YES_{tation} Mini is an ideal enterprise-wide solution.

YESstation Mini Hardware Specifications

Items

Processor
Input / Output connector support

Operating Systems
Display Resolution Et colors

Memory Support

Environment
Temperature
Relative Humidity
Operating Altitude Range
Power

Regulatory Compliance

Physical Characteristics
Dimensions (WxDxH)

Specifications

Sis 550
10/100 dual speed Ethernet, Twisted Pair (RJ45)
One parallel port (DB-25 Female connector)
Enhanced ps/2 keyboard and mouse interfaces
Two USB ports
Microsoft Windows CE.net; Linux
Supports 640x480, 800x600, 1024x768, 1280x1024 with high color (16 bits)
Flicker free, up to 85 Hz
SDRAM -- 64 MB (max. 256MB)
Flash memory: DOC 16MB standard (max. 64MB)
Operating : 5° C to 40° C (41° F to 104° F)
Storage : -40° C to 60° C (-4° F to 140° F)
90% maximum, non-condensing
0 to 10,000 feet (0 to 3050 meters)
Full range auto-sensing 100 ~ 240 VAC at 50 Hz ~ 60 Hz; 10 Watts
UL, C-UL, TUV; FCC Class B; CE mark
7.75 x 6.0 x 1.75 (Inches); Weight: 1.5 Pounds

FEATURE

	2205	2212	2213	2214
Retail Price (MSRP)	\$395	\$495	\$495	\$495
Configuration	Modular Logic Unit	Modular Logic Unit	Modular Logic Unit	Modular Logic Unit
Ports	Audio Parallel, PS2, USB(2)	Audio Parallel, PS2, USB(2)	Audio Parallel, PS2, USB(2)	Audio Parallel, PS2, USB(2)
Processor	SIS 550	SIS 550	SIS 550	SIS 550
Operating System	CE.NET	CE.NET	CE.NET	Linux
Presentation	Graphical	Graphical	Graphical	Graphical
RAM	64MB	64MB	64MB	64MB
Disk On Chip	16MB	16MB	16MB	32MB
Emulation Support	None	PowerTerm, 5250e/3270e, ASCII	YESterm, 5250e/3270e	YESterm, 5250e/3270e, Xterm
122 Keyboard Support	Yes	Yes	Yes	Yes
5250/3270 GUI	No	Yes	Yes	Yes
5250/3270 Network Printing	No	No	Yes	Yes
IBM Printing	N/A	SCS	SCS	SCS
Local Browser	IE 5.5	IE 5.5	IE 5.5	Netscape 4.78
ICA Citrix	Yes	Yes	Yes	Yes
RDP Windows	Yes	Yes	Yes	Yes
Java Virtual Machine	No	No	No	Yes
Scaleable Windows	RDP/ICA Only	RDP/ICA Only	RDP/ICA Only	All Sessions
PDF Reader	Yes	Yes	Yes	Yes
Flash Plug In	MS Media Player	MS Media Player	MS Media Player	Macro Media
MS Office Viewer	Yes	Yes	Yes	No
Max Emulation Sessions	None	10 w/64MB RAM	4	4
Wake On LAN	Yes	Yes	Yes	Yes
Dial Up Support	RAS, ICA, Internet	RAS, ICA, Internet	RAS, ICA, Internet	RAS, ICA, Internet
MS VPN Client	Yes	Yes	Yes	Yes
Wireless Support	External	External	External	External
Touch Screen Support	Yes	Yes	Yes	No
USB Support	Storage, KB, Mouse	Storage, KB, Mouse	Storage, KB, Mouse	Storage, KB, Mouse
SNMP Client	Yes	Yes	Yes	Yes
Central Management	YESmanager + RD	YESmanager + RD	YESmanager + RD	YESmanager + RD

Authorized Distributor

